

Visit [www.chemgrout.com](http://www.chemgrout.com)



## CG-680 Series

### CG-680, CG-685 & CG-6880, CG-6885 Large Colloidal Grout Plants

45 gpm; single or double pump models;  
skid mounted or trailer-mount

Specially designed as a highly mobile or portable high capacity plant, the CG-680 series machines are ideal for large, heavy construction sites. The double pump models (CG-6880 and 6885) minimize downtime and enhance efficiency with reserve second pump for emergency standby, which may (upon request) be configured as a water testing pump. The skid mounted units are available with diesel or electric power. Trailer mounted option is powered by diesel.

#### Specifications

##### PUMP

680, 685	31.8 single pump, progressing cavity
6880, 6885	(2) 31.8 double pump, progressing cavity
Output/Pressure	1 to 45 gpm, 261 psi

##### COLLOIDAL MIXER

Mix Tank	17 c.f. with bottom cleanout
Mixing Pump	2 x 3 x 12 diffuse-type centrifugal
Holding Tank	17 c.f. paddle agitating

##### DRIVE POWER

680, 6880 Skid Mount	
Hydraulic	25 GPM, 2000 psi
Electric	230/460, 102/52 Amp (40 HP)
Diesel	32 HP
685, 6885 Trailer Mount	
Diesel	32 HP

##### PHYSICAL SPECIFICATIONS

680, 685 Skid Mount Dimensions	96"L x 60"W x 60"H
6880, 6885 Trailer Mount Dimensions	120"L x 84"W x 84"H
680, 6880 Skid Mount Weight	4200 and 4700 pounds
685, 6885 Trailer Mount Weight	5500 and 6000 pounds

